

# FW01-NAP: Routine For Extended Sleep Delays

## Description

**NAP** is a routine we wrote to sleep the PIC for an extended period of time to conserve battery life.

## What's Included

<b>NAP.INC</b>	The sleeping routine
<b>NAP_DEMO.ASM</b>	Demo program
<b>WAIT.INC</b>	1mS delay routine
<b>P16F84.INC</b>	PIC16F84 definitions
<b>NAP_DEMO.HEX</b>	Assembled demo program
<b>NAP.PDF</b>	This file
<b>31026A.PDF</b>	Microchip paper on WDT and SLEEP

## Operation/Usage

**NAP** uses the watchdog timer (WDT) to wake up the PIC from a SLEEP command. The duration of these little pauses is dependent on the postscaler value assigned to the WDT. The default WDT timeout is 18mS; this can be extended to a maximum value of approx. 2.3 seconds with a postscaler value of 1:128 (18mS x 128 = 2.3S).

To extend this to a useful sleep delay, we have a defined a 16 bit counter NAPHI:NAPLO which is decremented each time the WDT wakes up the PIC. If NAPHI:NAPLO = zero then the MAIN loop is

executed; if not zero then the PIC is just put back to sleep.

To set the duration of the extended sleep, the user sets the value of NAPHI:NAPLO in **NAP.INC**. This number times the WDT timeout period (set by WDT postscaler) defines the total time spent asleep. You can see that a very long sleep delay can be defined in this manner.

NAP is invoked by: **GOTO NAP**

## Testing

**NAP\_DEMO.ASM** is a program that demonstrates the NAP routine. It switches on RB0 for 250mS (delay set by **WAIT.INC** routine), back off, then branches to **NAP.INC** where a 5 count sleep duration is setup in NAPHI:NAPLO defining an approx. 11.5S extended sleep (2.3S x 5 = 11.5S). MAIN repeats thereafter.

A Rapid18 PCB was used to test this program. RB0 was attached to BUZZ to activate the buzzer on the board when RB0 was high. A PIC16F84 was programmed with **NAP\_DEMO.HEX** and installed on the PCB.

When power was applied to the PCB the buzzer approximately every 15S. Not the 11.5S we had predicted, but close. Note that the WDT RC oscillator is temperature sensitive and timing calculations will be approximate--a bit of experimentation may be in order to get the precise sleep delay you desire.

## Contact Us

We maintain a website where you can get information on our products, obtain literature, and download support files. Visit us online at:

***www.dhmicro.com***

Email your technical support questions to **support@dhmicro.com**. We try to respond to your questions within an hour if it is received Monday through Friday between the hours of 8am to 5pm (Mountain Time).

For sales questions or to place an order, direct your emails to **sales@dhmicro.com**. Refer to the order form and price list available on our website for product pricing, shipping rates, payment instructions, and for other info we need to complete your order.

Our mailing address:

**DH MicroSystems, Inc.**  
P.O. Box 2272  
Pocatello, ID 83206-2272

**Disclaimer:** DH MicroSystems, Inc. reserves the right to modify its products or literature, or to discontinue any product at any time without prior notice. The customer is responsible for determining the suitability of any device for any application developed using DH MicroSystems, Inc. components.

**Copyright © 2003 DH MicroSystems, Inc.**

All trademarks mentioned in this document are the property of their respective companies.